



DEPARTMENT OF REGULATORY AND ECONOMIC RESOURCES (RER)  
BOARD AND CODE ADMINISTRATION DIVISION  
**NOTICE OF ACCEPTANCE (NOA)**

MIAMI-DADE COUNTY  
PRODUCT CONTROL SECTION  
11805 SW 26 Street, Room 208  
Miami, Florida 33175-2474  
T (786) 315-2590 F (786) 315-2599  
[www.miamidade.gov/economy](http://www.miamidade.gov/economy)

Horton Automatics Division of Overhead Door  
4242 Baldwin Boulevard  
Corpus Christi, TX 78405

**SCOPE:**

This NOA is being issued under the applicable rules and regulations governing the use of construction materials. The documentation submitted has been reviewed and accepted by Miami-Dade County PERA -Product Control Section to be used in Miami Dade County and other areas where allowed by the Authority Having Jurisdiction (AHJ).

This NOA shall not be valid after the expiration date stated below. The Miami-Dade County Product Control Section (In Miami Dade County) and/or the AHJ (in areas other than Miami Dade County) reserve the right to have this product or material tested for quality assurance purposes. If this product or material fails to perform in the accepted manner, the manufacturer will incur the expense of such testing and the AHJ may immediately revoke, modify, or suspend the use of such product or material within their jurisdiction. PERA reserves the right to revoke this acceptance, if it is determined by Miami-Dade County Product Control Section that this product or material fails to meet the requirements of the applicable building code.

This product is approved as described herein, and has been designed to comply with the Florida Building Code, including the High Velocity Hurricane Zone.

**DESCRIPTION: Series "110 " (Sx-O) Aluminum Automatic Sliding Door w/ Breakout**

**APPROVAL DOCUMENT:** Drawing No. **040709-L REV 4**, titled "Series 2001/110 Impact Single Slide", sheets 1 through 5 of 5, prepared by manufacturer, dated 11/25/09 and last revised on 09-11-15, signed and sealed by John E. Scates, P.E., bearing the Miami-Dade County Product Control Revision stamp with the Notice of Acceptance number and expiration date by the Miami-Dade County Product Control Section.

**MISSILE IMPACT RATING: Large and Small Missile Impact Resistant**

**Limitations:**

1. Not approved where water infiltration is required, unless protected by overhang complying w/FBC requirements
2. See partial breakout detail sheet 1 and glazing and optional muntin details in sheet 2.
3. See sheet 3 for anchor and substrates options. Applicable anchor edge distance to be measured from screw center line to the outer face of the substrate.
4. Electrical/ Electronic functions are not part of this approval and to be reviewed by appropriate Bldg. official.

**LABELING:** Each unit shall bear a permanent label with the manufacturer's name or logo, city, state and series and following statement: "Miami-Dade County Product Control Approved", noted herein.

**RENEWAL** of this NOA shall be considered after a renewal application has been filed and there has been no change in the applicable building code negatively affecting the performance of this product.

**TERMINATION** of this NOA will occur after the expiration date or if there has been a revision or change in the materials, use, and/or manufacture of the product or process. Misuse of this NOA as an endorsement of any product, for sales, advertising or any other purposes shall automatically terminate this NOA. Failure to comply with any section of this NOA shall be cause for termination and removal of NOA.

**ADVERTISEMENT:** The NOA number preceded by the words Miami-Dade County, Florida, and followed by the expiration date may be displayed in advertising literature. If any portion of the NOA is displayed, then it shall be done in its entirety.

**INSPECTION:** A copy of this entire NOA shall be provided to the user by the manufacturer or its distributors and shall be available for inspection at the job site at the request of the Building Official.

This NOA revises & renews NOA # **13-0530.15** and consists of this page 1 and evidence pages E-1, as well as approval document mentioned above.

The submitted documentation was reviewed by **Ishaq I. Chanda, P.E.**



NOA No. 15-0922.11  
Expiration Date: August 21, 2023  
Approval Date: April 07, 2016  
Page 1

4  
3/31/16

**Horton Automatics Division of Overhead Door**

**NOTICE OF ACCEPTANCE: EVIDENCE SUBMITTED**

**A. DRAWINGS**

1. Manufacturer's die drawings and sections (see files below)
2. Drawing No. **040709-L REV 4**, titled "Series 2001/110 Impact Single Slide", sheets 1 through 5 of 5, prepared by manufacturer, dated 11/25/09 and last revised on 09-11-15, signed and sealed by John E. Scates, P.E.

**B. TESTS (submitted under files #13-0530.15/#12-0801.10/#10-0322.17)**

1. Test reports on:
  - 1) Air Infiltration Test, per FBC, TAS 202-94
  - 2) Uniform Static Air Pressure Test, Loading per FBC TAS 202-94
  - 3) Water Resistance Test, per FBC, TAS 202-94 (Not conducted)
  - 4) Large Missile Impact Test per FBC, TAS 201-94
  - 5) Cyclic Wind Pressure Loading per FBC, TAS 203-94
  - 6) Forced Entry Test, per FBC 2411 3.2.1, TAS 202-94

along with installation diagram of an aluminum automatic sliding glass doors, prepared by Hurricane Testing Laboratories, Test Report No. **HTL-0322-1103-07** (phase 2, elevations 1 thru 4), dated 03/14/08 and revised on 06/12/08 by an addendum letter, signed and sealed by Vinu Abraham, P.E.

**C. CALCULATIONS**

1. Anchor verification calculations and structural analysis complying w/ FBC 2014 (5<sup>th</sup> edition), dated 09/11/15, prepared, signed and sealed by John E. Scates, P.E.
2. Glazing complies w/ ASTM E-1300-02, -04 & -09.

**D. QUALITY ASSURANCE**

1. Miami-Dade Department of Regulatory and Economic Resources (RER).

**E. MATERIAL CERTIFICATIONS**


1. Notice of Acceptance No. **12-1231.08** issued to Eastman Chemical Co. (MA) former Solutia, Inc. for their "**Saflex-CP Saflex HP Composite Glass @ interlayer w/ PET core**", expiring on 12/11/2018.

**F. STATEMENTS (All items except #1, submitted under files 12-0801.10/#10-0322.17)**

1. Statement letter of conformance to FBC 2014(5<sup>th</sup> Edition) & "No financial interest", dated SEP 11, 2015, signed & sealed by John E. Scates, P.E.
2. Addendum letter dated 06-12-08, issued by Hurricane Testing lab, signed and sealed by Vinu Abraham, P. E. (submitted under file #13-0530.15/#12-0801.10/ #08-0410.17)
3. Lab compliance as part of the above referenced test report.

**G. OTHER**

1. This NOA revises & renews NOA # 13-0530.15, expiring on August 21, 2023.



Ishag I. Chanda, P.E.


Product Control Examiner

NOA No. 15-0922.11

Expiration Date: August 21, 2023

Approval Date: April 07, 2016

NOTE:  
For fastener location and type see sheets 3  
The 1.6 wind load allowance was used  
in the wood anchor calculations.



NOTE:  
5 X SCREWS (ITEM 36) TO FASTEN FIXED  
PANEL TO FIXED CORNERBLOCK (ITEM  
14), 2 SCREWS MOUNTED 1.00\"/>


NOTE:  
SEE GLAZING DETAIL SEE SHEET 2

NOTE:  
FIXED PANEL'S BOTTOM RAIL (ITEM 9) TO BE  
SLIP FIT ON TO CORNER BLOCK (ITEM 14)


1/8\"/>

SEE SHEET 3 FOR  
ANCHOR DETAILS  
AND MIN. EDGE  
DISTANCE


VERTICAL SECTION  
DOOR SHOWN IN OPEN POSITION



EXTERIOR ELEVATION




FLOOR PLAN



THRESHOLD DETAIL

Locking Mechanism : 3point Locking Device Standard (24,25,27)  
(see sheet 4)




HORIZONTAL SECTION

# NOTES:

1. This product has been designed and tested to comply with the current Florida Building Code, including High Velocity Hurricane Zone (HVHZ).
2. Electrical/Electronic functions are not part of this approval and must be reviewed by appropriate building official.
3. See anchor installation details concerning types, substrate, edge distance, spacing and embedment on sheet 3.
4. 1x or 2x wood bucks by others must be secured properly to transfer loads using appropriate fasteners and quantities. Fasteners to secure wood buck must penetrate concrete or grouted CMU jamb substrate minimum 2.0\"/>

JOHN E. SCATES  
3121 FAIRGATE DR.  
CARROLLTON, TX 75007  
FL PE 51737



PRODUCT REVISED  
as complying with the Florida  
Building Code  
Acceptance No. 15-0922-11  
Expiration Date AUG 21, 2023  
By: [Signature]  
Impact Data Product Control

## Single Slide Doors

Where Water Infiltration Requirement is needed	Where Water Infiltration Requirement is NOT needed
Not Approved	± 80 PSF

Panel Width  
nom. door  
42-1/2"

Net Slide  
opening  
35 3/8"

Available Unit Sizes:  
7'-0\"/>


3 - Point Lock  
(See Sheet 4)

Series 110 Impact Slide


NO.	REVISIONS DESCRIPTION	DATE	ARCHITECT:
1	RELEASE FOR P.E. APPROVAL	11/25/08	CONTRACTOR:
2	REVISED AS PER P.E. MARK-UPS	12/28/09	SERIES: 2001/110 TYPE: "O-SX" & "SX-O"
3	REVISED FOR NOA RENEWAL	08/13/13	STYLE: NARROW FINISH:
4	REVISED FOR NOA	09/09/15	ACTUATION:
5			
6			
7			
8			

2001/110 Large & Small  
Impact Dwg. # 040709-L


A DIVISION OF OVERHEAD DOOR CORP. 4242 BALDWIN BOULEVARD CORPUS CHRISTI, TEXAS 78405-3399 361-888-5591 1-800-531-3111 FAX: 361-888-6510, 1-800-531-3108	JOHN E. SCATES 3121 FAIRGATE DR. CARROLLTON, TX 75007 FL PE 51737
DISTRIBUTOR: DWN: M. JONES P.O. # 1 CHK: A. NOGUEIRA DATE 08/13/13	REVISION 4




"SX" PANEL  
TOP PIVOT




"SX" PANEL  
BTM. PIVOT



LOCK BOLT DETAIL  
3-POINT LOCK



CONNECTION BLOCK  
WITH REINFORCEMENT  
STRIKE RAIL (SX)



CONNECTION BLOCK  
INTERLOCK RAIL (SX)  
INTERLOCK RAIL (O)  
FIXED RAIL (O)

WEATHERSEALS:  
C350 NOSING SEAL  
C524-FL SIDE PANEL BOTTOM SEAL  
C293 WEATHER SEAL


HARDWARE:  
C883 THRESHOLD/HEADER BOLT

SCHLEGEL CORP. SKIRTING SEAL #1104-5101  
FELTON NYLON BRISTLE #490621  
SCHLEGEL CORP. #8430-5016-7

ADAMS-RITE #4015


\* 9/16" thick (nominal) Laminated Glass consisting of the following components:  
\* Saflex CP: Composite glass interlay w/ PET core by Eastman Chemical Co. (MA)

\* Interior wet glazed with Dow Corning 995  
\* Exterior side snap-in glazing bead with vinyl wedge  
\* Minimum glass bite 9/16"




GLAZING DETAIL

SANTOPRENE GASKET (ITEM 45) MIN 67  
SHORE A DUROMETER FROM CENTRAL  
PLASTICS INC.



MUNTIN OPTION

JOHN E. SCATES  
3121 FAIRGATE DR.  
CARROLLTON, TX 75007  
FL PE 51737




PRODUCT REVISED  
as complying with the Florida  
Building Code  
Acceptance No. 15-0922.11  
Expiration Date 8/21/2023  
By: [Signature]  
Product Control

Series 110 Impact Slide

NO.	REVISIONS DESCRIPTION	DATE	ARCHITECT:
1	RELEASE FOR P.E. APPROVAL	11/23/09	CONTRACTOR:
2	REVISED AS PER P.E. MARK-UPS	12/29/09	SERIES: 110 TYPE: "O-SX" & "SX-O"
3	REVISED FOR NOA REVIEW	08/13/13	STYLE: NARROW FINISH:
4	REVISED FOR NOA	09/09/15	ACTUATION:
5			
6			
7			
8			


Misc. Details  
Dwg. No. 040709-L

A DIVISION OF OVERHEAD DOOR CORP.  
4242 BALDWIN BOULEVARD  
CORPUS CHRISTI, TEXAS 78405-3399  
361-888-5591 1-800-531-3111  
FAX: 361-888-6510, 1-800-531-3108  
Horton  
AUTOMATIC  
JOB: MEIRO-DADE  
LOCATION:  
DISTRIBUTOR:  
OWN: M. JONES P.O. 1  
CHK: A. NADGOUDA DATE: 04/07/09 REVISION: 4



The frame must be shimmed with a type of shim complying with the Florida Building Code and is capable of resisting the frame's rotation 1/4" thk. Max

The 1.6 wind load allowance was used in the wood anchor calculations.



#### HEADER

Steel (0.125" Thick, Fy=36 KSI) - INTERCORP #14 Steel HWH Self-Drilling Screw (Grade 5), 0.625" Min. Edge Distance (Full Thread Engagement)  
 Aluminum(0.125" Thick Min./6063-T5) - 1/4"-14 HWH Sheetmetal Screw (Grade 5), 1" Min. Edge Distance. (Full Thread Engagement)

#### JAMBS

Steel (0.125" Thick, Fy=36 KSI) -ITW TEKS SCREW (Grade 5) #14-20, HWH Self-Drilling Screw 0.625" Minimum Edge Distance (Full Thread Engagement)

Concrete(3350 PSI) - Crete-Flex SS4 1/4" HWH Concrete Screw/Anchor, 1.75" Embed, 2.5" Min. Edge Distance

Masonry(Solid CMU ASTM C-90 Block) - Crete-Flex SS4 1/4" HWH Concrete Screw/Anchor, 1.25" Embed, 2.5" Min. Edge Distance

Aluminum(0.125" Thick Minimum/6063-T5) - 1/4"-14 HWH Sheetmetal Screw (Grade 5), 1" Min. Edge Distance. (Full Thread Engagement)  
 Wood(#2 SYP)-1/4" x 4" Long Lag Bolt - Grade 5, 2.75" Minimum Penetration, 1" Minimum Edge Distance. Minimum Buck (2) 2XB W/Min G = .55.


#### THRESHOLD

Steel (0.125" Thick, Fy=36 KSI)- ITW TEKS SCREW #14-20 PFH w/Wings Self-Drilling Screw (Grade 5), 0.625" Minimum Edge Distance (Full Thread Engagement)

Concrete(3350 PSI)- Crete-Flex SS4 FH 1/4" Concrete Screw 1.75" Embed, 2.5" Minimum Edge Distance

Aluminum(0.125" Thick Minimum/6063-T5) - 1/4"-14 FH Sheetmetal Screw (Grade 5), 1" Minimum Edge Distance (Full Thread Engagement)

JOHN E. SCATES  
 3121 FAIRGATE DR.  
 CARROLLTON, TX 75007  
 FL PE 51737



**PRODUCT REVISED**  
 as complying with the Florida Building Code  
 Acceptance No. 15-09722.11  
 Expiration Date 8/21/2023  
 [Signature] Product Control


Series 110 Impact Slide Anchor Locations

NO.	REVISIONS DESCRIPTION	DATE	ARCHITECT:
1	RELEASE FOR P.E. APPROVAL	11/23/09	CONTRACTOR:
2	REVISED AS PER P.E. MARK-UPS	12/29/09	SERIES: 110
3	REVISED FOR NOA RENEWAL	08/13/13	STYLE: NARROW
4	REVISED FOR NOA	09/06/15	FINISH:
			ACTUATION:

A DIVISION OF OVERHEAD DOOR CORP.  
 4242 BALDWIN BOULEVARD  
 CORPUS CHRISTI, TEXAS 78405-3399  
 361-888-5591 1-800-531-3111  
 FAX: 361-888-6510, 1-800-531-3108  
**Horton**  
 AUTOMATION  
 JOB: METRO-DADE  
 LOCATION:  
 DISTRIBUTOR:  
 DWN: M.JONES P.O. #  
 CHK: A.NADGOUDA DATE: 04/07/09 SHEET 3 OF 5  
 REVISION 4

ITEM #	HORTON PART NUMBER	DESCRIPTION
1	C03600.005AB	ALUMINUM EXTRUSION: HEADER
2	C03601.002AB	ALUMINUM EXTRUSION: HEADER FACEPLATE
3	C00358.000R	ALUMINUM EXTRUSION: ASTRAGAL
4	C00314.0000	ALUMINUM EXTRUSION: INTERLOCK TOP
5	C00327.0000AB	ALUMINUM EXTRUSION: INTERLOCK LOWER
6	C00337.000R	ALUMINUM EXTRUSION: TOP RAIL (SX) & MUNTIN (SX/O)
7	C00379.001ABC	ALUMINUM EXTRUSION: GLASS STOP
8	C00336.0001	ALUMINUM EXTRUSION: BOTTOM RAIL (SX)
9	C00325.0002	ALUMINUM EXTRUSION: BOTTOM RAIL (O)
10	C00315.0000	ALUMINUM EXTRUSION: TRACK FILLER
11	C00330.0001	ALUMINUM EXTRUSION: BOTTOM GUIDE
12	C00386.0001	ALUMINUM EXTRUSION: ADAPTOR
13	C02801.0000	ALUMINUM EXTRUSION: TOP RAIL (O)
14	C02899.0002	ALUMINUM EXTRUSION: CORNER BLOCK (USED AS REINFORCEMENT)
15	C00390.0000	ALUMINUM EXTRUSION: THRESHOLD 7"
16	C00351.0000	ALUMINUM EXTRUSION: JAMB TUBE 4" X 1-3/4 W/ POCKET
17	C00335.000R	ALUMINUM EXTRUSION: VERTICAL RAIL (SX/O INTERLOCK) (O FIXED)
18	C00363.0000	ALUMINUM EXTRUSION: VERTICAL RAIL (SX STRIKE)
19	C00818.000R	BAR TORSION
20	C00524.00FL	WEATHERSEAL BRUSH (FELTON #490621)
21	C00350.0000	NOSING SEAL SCHLEGEL #1104-5101
22	C00397.0000	ADAPTER FOR C00389.01FL
23	C00293.0000	WEATHER SEAL BRUSH SCHLEGEL #8430-5016-7
24	C00454.0000	LOCK, ADAMS RITE MS1850S W/ ADAMS RITE 4015 HEADER/THRESHOLD BOLT
25	C00463.0000	THUMBTURN ADAMS RITE 4066
26	C02098.0000	SECURITY POST; 1/2" O.D. X 3/4" LG X .083" WALL ALUM. TUBE
27	C00883.0000	3/8 HEXT BOLT ADAMS RITE 4015 EXTENDING INTO HEAD AND SILL 1/2"
28	C00843.01FL	BOTTOM GUIDE DOOR MOUNTED
29	C00844.01FL	BOTTOM GUIDE DOOR MOUNTED
30	C03638.0000	HEADER & FACEPLATE SUPPORT
31	C00371.000R	WEATHERSTRIP; PANEL TO JAMB
32	C00664.0001	#8 X 3/4 FHSMS
33	C09653.0000	#10 X 3/4 FHSMS
34	C00404.0000	1/4-20 LOCK NUT
35	C00417.0000	#14 X 1-1/2 HWSMS
36	C00449.0000	#10-24 X 1 FHMS
37	C03682.0006	DRIVE WHEEL ASSEMBLY
38	C03681.0001	IDLER WHEEL ASSEMBLY
39	C08151.0000	1/4-20 X 1 FHMS
40	C08150.0000	1/4-20 X 3/4 HHMB

ITEM #	HORTON PART NUMBER	DESCRIPTION
41	C00537.000R	CORNER BLOCK (SX TOP) (SX/O MUNTIN)
42	C09490.0001	CORNER BLOCK (O TOP)
43	C00536.0001	CORNER BLOCK (SX BOTTOM)
44	C09582.0002	CORNER BLOCK (O BOTTOM)
45	C00341.0001	VINYL GLAZING BULB - EXONMOBIL CHEMICAL SANTOPRENE EXTRUDED BY CENTRAL CHEMICAL INC.
46	C00289.0000	TRACK CAP
47	C00389.01FL	INTERLOCK SEAL SCHLEGEL #7595-6011-0
48	C01905.0000	STEEL TUBE (1-1/4" X 1-1/4" X 3/16" X 80.50") A-36
49	C00437.000AB	#10-24 X 1/2 FHSMS
50	C00353.0000	COVER; RECESS - JAMB
51	C01485.0001	SILICONE; GLAZING (#995 DOW CORNING)
52	C00538.000R	BACKUP PLATE; CRS



NO.	REVISIONS DESCRIPTION	DATE	ARCHITECT:
1	RELEASE FOR P.E. APPROVAL	11/23/09	CONTRACTOR:
2	REVISED AS PER P.E. MARKUPS	12/25/09	SERIES 2001/110 TYPE "O-SX" & "SX-O"
3	REVISED FOR NOA REVIEW	04/13/12	STYLE: NARROW FINISH:
4	REVISED FOR NOA	08/09/13	ACTUATION:
5			
6			
7			
8			

Bill of materials  
Dwg. No. 040709-L

JOHN E. SCATES  
3121 FAIRGATE DR.  
GARROLLTON, TX 75007  
FL PE 51737

*John E. Scates*  
9/11/15

JOHN E. SCATES  
LICENSE  
No. 51737  
STATE OF  
FLORIDA  
PROFESSIONAL ENGINEER


**PRODUCT REVISED**  
as complying with the Florida  
Building Code  
Acceptance No. 15-0922-11  
Expiration Date 8/21/2023  
*E. Ishag I. Chaudhry*  
Metro Dade Product Controls

A DIVISION OF OVERHEAD DOOR CORP.  
4242 BALDWIN BOULEVARD  
CORPUS CHRISTI, TEXAS 78405-3399  
361-888-5591 1-800-531-3111  
FAX: 361-888-6510, 1-800-531-3108








**Horton**

JOB **METRO-DADE**  
LOCATION:  
DISTRIBUTOR:  
OWN: M. JONES P.O. #  
CHKA NADCOUDA DATE 04/07/09 REVISION 4


SHEET 4 of 5



6" X 8"  
(152.4) (203.2)  
ASSEMBLED











ASTM A-36 STEEL




SANTOPRENE U.V. GRADE 121  
BULB: SANTOPRENE 121-67W175  
DUROMETER SHORE 67A  
BASE: SANTOPRENE 101-87  
DUROMETER SHORE 87A

ALL EXTRUSIONS ARE 6063-T5 UNLESS  
OTHERWISE NOTED & t min=1/8"



JOHN E. SCATES  
3121 FAIRGATE DR.  
CARROLLTON, TX 75007  
FL PE 61737



PRODUCT REVISED  
as complying with the Florida  
Building Code  
Acceptance No. 15-0722-11  
Expiration Date 04/21/2023  
By: [Signature]  
Metro-Deer Product Control

Series 110 Impact Slide

NO.	REVISIONS DESCRIPTION	DATE	ARCHITECT:
1	RELEASE FOR P.E. APPROVAL	11/23/08	CONTRACTOR:
2	REVISED AS PER P.E. MARKUPS	11/29/08	SERIES: 110
3	REVISED FOR NOA RENEWAL	08/13/13	STYLE: NARROW
4	REVISED FOR NOA	09/09/15	FINISH:
5			ACTUATION:
6			
7			
8			

Extrusion chart  
Dwg. No. 040709-L

A DIVISION OF OVERHEAD DOOR CORP.  
4242 BALDWIN BOULEVARD  
CORPUS CHRISTI, TEXAS 78405-3399  
361-888-5591 1-800-531-3111  
FAX: 361-888-6510, 1-800-531-3108  
JOB: METRO-DADE  
LOCATION:  
DISTRIBUTOR:  
OWN: M. JONES P.O. #  
DATE: 04/07/09 REVISION: 4